

isc N-Channel MOSFET Transistor

IRFB7546, IIRFB7546

• FEATURES

- Static drain-source on-resistance:
 $R_{DS(on)} \leq 7.3m\Omega$
- Enhancement mode
- Fast Switching Speed
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

• DESCRIPTION



- Synchronous Rectifier applications
- Resonant mode power supplies
- Battery powered circuits

• ABSOLUTE MAXIMUM RATINGS(T_a=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
V _{DSS}	Drain-Source Voltage	60	V
V _{GS}	Gate-Source Voltage	±20	V
I _D	Drain Current-Continuous	75	A
I _{DM}	Drain Current-Single Pulsed	300	A
P _D	Total Dissipation @T _c =25°C	99	W
T _j	Max. Operating Junction Temperature	175	°C
T _{stg}	Storage Temperature	-55~175	°C

• THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
R _{th(ch-c)}	Channel-to-case thermal resistance	1.52	°C/W
R _{th(ch-a)}	Channel-to-ambient thermal resistance	62	°C/W



isc N-Channel MOSFET Transistor
IRFB7546,IIRFB7546
ELECTRICAL CHARACTERISTICS

 T_C=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V; I _D = 250μA	60			V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} ; I _D =100 μ A	2.1		3.7	V
R _{DS(on)}	Drain-Source On-Resistance	V _{GS} =10V; I _D =45A			7.3	mΩ
I _{GSS}	Gate-Source Leakage Current	V _{GS} =± 20V			±100	nA
I _{DSS}	Drain-Source Leakage Current	V _{DS} =60V; V _{GS} = 0V			1	μ A
V _{SD}	Diode forward voltage	I _S =45A, V _{GS} = 0 V			1.2	V