

N-Channel Enhancement Mode Power MOSFET


MTB015N10QQ8

BV_{DSS}	100V
I_D @ T_A=25°C, V_{GS}=10V	10A
I_D @ T_C=25°C, V_{GS}=10V	12.2A
R_{DS(ON)}@ V_{GS}=10V, I_D=10A	12.6 mΩ (typ)
R_{DS(ON)}@ V_{GS}=4.5V, I_D=8A	17.4mΩ (typ)


Features

- Single Drive Requirement
- Low On-resistance
- Fast Switching Characteristic
- Repetitive Avalanche Rated
- Pb-free & Halogen-free package

Symbol




Outline



Ordering Information

Device	Package	Shipping
MTB015N10QQ8-0-T3-G	SOP-8 (RoHS compliant & Halogen-free package)	2500 pcs / Tape & Reel





Absolute Maximum Ratings (Tc=25°C, unless otherwise noted)

Parameter	Symbol	Limits	Unit	
Drain-Source Voltage	V _{DS}	100	V	
Gate-Source Voltage	V _{GS}	±20		
Continuous Drain Current @ T _c =25°C, V _{GS} =10V	I _D	12.2	A	
Continuous Drain Current @ T _c =100°C, V _{GS} =10V		7.7		
Continuous Drain Current @ T _A =25°C, V _{GS} =10V	I _{DSM}	10		
Continuous Drain Current @ T _A =70°C, V _{GS} =10V		8		
Pulsed Drain Current	I _{DM}	40 *1		
Avalanche Current	I _{AS}	10		
Avalanche Energy @ L=5mH, I _D =10A, R _G =25Ω	E _{AS}	250 *2	mJ	
Repetitive Avalanche Energy @ L=0.05mH	E _{AR}	1.6 *3		
Total Power Dissipation	P _D	T _c =25 °C	5.0	W
		T _c =100 °C	2.0	
	P _{DSM}	T _A =25 °C	3.1	
		T _A =70 °C	2.0	
Operating Junction and Storage Temperature	T _j , T _{stg}	-55~+150	°C	

Note : *1. Pulse width limited by maximum junction temperature.

*2. 100% tested by conditions of L=2mH, I_{AS}=10A, V_{GS}=10V, V_{DD}=25V

*3. Duty cycle ≤ 1%

Thermal Data

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-case	R _{th,j-c}	25	°C/W
Thermal Resistance, Junction-to-ambient (Note)	R _{th,j-a}	40	

Note : 40°C / W when mounted on a 1 in² pad of 2 oz copper, t≤10s; 125°C/W when mounted on minimum pad.

Characteristics (Tc=25°C, unless otherwise specified)


Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Static					
B _V DSS	100	-	-	V	V _{GS} =0V, I _D =250μA
V _{GS(th)}	1.0	-	2.5		V _{DS} = V _{GS} , I _D =250μA
G _F S	-	19	-	S	V _{DS} =10V, I _D =10A
I _{GSS}	-	-	±100	nA	V _{GS} =±20V
I _{DSS}	-	-	1	μA	V _{DS} =100V, V _{GS} =0V
	-	-	10		V _{DS} =100V, V _{GS} =0V, T _j =85°C
*R _{DS(ON)}	-	12.6	17	mΩ	V _{GS} =10V, I _D =10A
	-	17.4	24		V _{GS} =4.5V, I _D =8A
Dynamic					
Q _g (V _{GS} =10V) *1, 2	-	49.9	-	nC	V _{DS} =80V, I _D =10A, V _{GS} =10V
Q _g (V _{GS} =4.5V) *1, 2	-	33.7	-		
Q _{gs} *1, 2	-	5.4	-		
Q _{gd} *1, 2	-	24.8	-		

Characteristics (Cont. Tc=25°C, unless otherwise specified)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Dynamic					
Ciss	-	1384	-	pF	V _{DS} =25V, V _{GS} =0V, f=1MHz
Coss	-	239	-		
Crss	-	214	-		
t _{d(ON)} *1, 2	-	15.8	-	ns	V _{DS} =50V, I _D =10A, V _{GS} =10V, R _G =3 Ω
t _r *1, 2	-	31.4	-		
t _{d(OFF)} *1, 2	-	47.6	-		
t _f *1, 2	-	22.2	-		
R _g	-	1	-	Ω	f=1MHz
Source-Drain Diode Ratings and Characteristics					
V _{SD} *1	-	0.82	1.2	V	I _S =10A, V _{GS} =0V
t _{rr}	-	42	-	ns	I _F =10A, dI _F /dt=100A/μs
Q _{rr}	-	52	-	nC	

Note : *1.Pulse Test : Pulse Width ≤300μs, Duty Cycle≤2%
 *2.Independent of operating temperature
 *3.Pulse width limited by maximum junction temperature.


Recommended Soldering Footprint






Typical Characteristics


Typical Output Characteristics




Brekdown Voltage vs Ambient Temperature




Static Drain-Source On-State resistance vs Drain Current




Reverse Drain Current vs Source-Drain Voltage



Static Drain-Source On-State Resistance vs Gate-Source Voltage




Drain-Source On-State Resistance vs Junction Temperature




Typical Characteristics(Cont.)


Capacitance vs Drain-to-Source Voltage




Threshold Voltage vs Junction Temperature




Forward Transfer Admittance vs Drain Current




Gate Charge Characteristics



Maximum Safe Operating Area




Maximum Drain Current vs Junction Temperature






Typical Characteristics(Cont.)


Typical Transfer Characteristics




Single Pulse Power Rating, Junction to Ambient
 (Note on page 2)




Transient Thermal Response Curves



Reel Dimension




Carrier Tape Dimension



Recommended wave soldering condition


Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds

Recommended temperature profile for IR reflow


Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (Tsmax to Tp)	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(Ts min)	100°C	150°C
-Temperature Max(Ts max)	150°C	200°C
-Time(ts min to ts max)	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (Tl)	183°C	217°C
- Time (tl)	60-150 seconds	60-150 seconds
Peak Temperature(Tp)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

SOP-8 Dimension



DIM	Millimeters		Inches		DIM	Millimeters		Inches	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	1.350	1.750	0.053	0.069	E	3.800	4.000	0.150	0.157
A1	0.100	0.250	0.004	0.010	E1	5.800	6.200	0.228	0.244
A2	1.350	1.550	0.053	0.061	e	1.270 (BSC)		0.050 (BSC)	
b	0.330	0.510	0.013	0.020	L	0.400	1.270	0.016	0.050
c	0.170	0.250	0.006	0.010	θ	0	8°	0	8°
D	4.700	5.100	0.185	0.200					

Notes: 1. Controlling dimension: millimeters.
 2. Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.
 3. If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material:

- Lead: Pure tin plated.
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0.

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.