


PCB LAYOUT
(Top View)



Material:

- PBT Glass Filled (UL 94V-0)
- Soldering temperature: 235°C
- Color: Black
- Spring Wire: 0.45mm Dia. Phosphor Bronze Gold plating over Nickel
- Shielded: Brass plating Nickel
- Temperature range: -40°C / +85°C
- Durability: 500 Mating cycles min.

Electrical:

- Insulation resistance: 500MΩ min.
- Conductor resistance: 20mΩ max.
- Rating current: 1.5A max.
- Dielectric voltage: 1,000V rms 60 Sec. min.

Unit: mm



Scale	Free					Date	Name	Title Modular Jack PCB 8P8C, 90° side entry, 6μ"
TOLERANCE						Drawn	Wilson	
X.XX	±0.25					Approved	Groll	ASSMANN WSW-No. A-2004-2-4-LP-N-R
X.XXX	±0.13							Drawing-No.
X.XXXX	±0.05							rev00
DIM	TOL							Replace
X.°	±X°							Sheet
X.X°	±X°							1/1
Angle	TOL	Id.	Modification	Date	Name	1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us		