

CUS1500M-48 New Product



Sales Region	Worldwide (except Japan)
Series	CUS-M
Status	Production
Feature	for Medical instruments
Option	
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics	
Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 340V
Efficiency	88% Typ.
Rated Output Voltage[DC]	48V
Output Voltage Range[DC]	40.8 to 52.8V
Maximum Output Current	32A
Maximum Output Power	1536W

Cases Shape & Size	
Case'□ shape	Unit
Width(W)	127mm Nom.
Height(H)	63mm Nom.
Depth(D)	261mm Nom.
Weight	3000g Typ.

Other	
Operating Temp. Range	-20 to 60°C
Cooling	Blower fan cooling
Safety Standard(Certified)	UL60950-1
	CSA60950-1
	EN60950-1
	UL62368-1
	CSA62368-1
	EN62368-1
	ES60601-1 3rd Edition
	CSA C22.2 No.60601-1 3rd Edition
Safety Standard(Conformed)	EN60601-1 3rd Edition
	EN62477-1 (OVCIII)
	Den-an Appendix 12

